

Description

diameter: 3/16", grip range: 0.251" - 0.312", bulbed, universal head, 5056 aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2249-6-5](#)

SKU / Model:	CR2249605
Minimum Qty (MOQ):	100
NSN:	5320-00-779-0334
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N CR2249-6-05 Specifications

Fastener Length:	0.479 Inches Minimum And 0.499 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.201 Inches Minimum And 0.205 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Shear Strength:	1390 Single Pounds Per Square Inch
Material:	Aluminum Alloy 5056 Sleeve
Material:	Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ring
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2249-6-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.