

**Description**

diameter: 3/16", grip range: 0.376" - 0.437", bulbed, universal head, 5056 aluminum sleeve, steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR2249-6-7](#)

SKU / Model:

CR2249607

Minimum Qty (MOQ):

100

NSN:

5320-00-490-2237

ECCN:

EAR99

National Motor Freight:

013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N CR2249-6-07 Specifications

<b>Fastener Length:</b>	0.603 Inches Minimum And 0.623 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.201 Inches Minimum And 0.205 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.376 Inches Minimum And 0.437 Inches Maximum
<b>Material:</b>	Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Locking Ring
<b>Surface Treatment:</b>	Anodize Sleeve
<b>Surface Treatment:</b>	Cadmium Stem And Chromate Stem
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2 Fed Spec All Treatment Responses Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2249-6-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.