

## P/N CR2249-6-2

### **Description**

Fastener Length: 19/64", CR2249 series rivet

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

#### CR2249-6-02

SKU / Model:	CR224962
Minimum Qty (MOQ):	100
NSN:	5320-00-939-1606
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



<sup>\*</sup> See page 2 for technical characteristics

# **P/N CR2249-6-2 Specifications**

Fastener Length:	0.287 Inches Minimum And 0.307 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.200 Inches Minimum And 0.204 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Shear Strength:	1390 Single Pounds Per Square Inch
Special Features:	Lock Ring Nickel-copper Alloy Qq-n-281
Material:	Aluminum Alloy 5056 Sleeve
Material:	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material:	Steel Comp E4340 Stem Or Steel Comp 4340 Stem Or Steel Comp 8740 Stem
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Stem Or Mil-s-5000 Mil Spec 2nd Material Response Stem Or Mil-s-6049 Mil Spec 3rd Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ring
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1738 Professional/industrial Association Standard

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/CR2249-6-2">https://military-fasteners.com/rivets/blind+rivets/CR2249-6-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR2249-6-2">https://military-fasteners.com/rivets/blind+rivets/CR2249-6-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR2249-6-2">https://military-fasteners.com/rivets/blind+rivets/CR2249-6-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/CR2249-6-2">https://military-fasteners.com/rivets/blind+rivets/CR2249-6-2</a> and selecting the quantity you want then