

Description

Fastener Length: 27/64", CR2249 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR2249-6-04](#)

SKU / Model:	CR224964
Minimum Qty (MOQ):	100
NSN:	5320-00-779-0301
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N CR2249-6-4 Specifications

Fastener Length:	0.415 Inches Minimum And 0.435 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.201 Inches Minimum And 0.205 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	1390 Single Pounds Per Square Inch
Special Features:	Lock Ring Nickel-copper Alloy Qq-n-281
Material:	Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ring
Surface Treatment:	Anodize Sleeve And Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1738 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2249-6-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.