

P/N CR2263-4-04

Description

diameter: 1/8", grip range: 0.188" - 0.250", wiredaw, universal head, 5056 aluminum sleeve, 7075 aluminum stem, CR2263 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CR2263-4-4

SKU / Model:	CR2263404
Minimum Qty (MOQ):	100
NSN:	5320-00-121-3045
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



^{*} See page 2 for technical characteristics

P/N CR2263-4-04 Specifications

Fastener Length:0.385 Inches MaximumHead Style:UniversalHead Height:0.054 Inches Minimum And 0.064 Inches MaximumShank Diameter:0.124 Inches Minimum And 0.128 Inches MaximumShank Style:Self-plugging Mechanically Locked StemHead Major Diameter:0.238 Inches Minimum And 0.262 Inches MaximumExpansion Device:Serrated Stem-type WGrip Length:0.188 Inches Minimum And 0.250 Inches Maximum
Head Height: 0.054 Inches Minimum And 0.064 Inches Maximum Shank Diameter: 0.124 Inches Minimum And 0.128 Inches Maximum Shank Style: Self-plugging Mechanically Locked Stem Head Major Diameter: 0.238 Inches Minimum And 0.262 Inches Maximum Expansion Device: Serrated Stem-type W
Shank Diameter:0.124 Inches Minimum And 0.128 Inches MaximumShank Style:Self-plugging Mechanically Locked StemHead Major Diameter:0.238 Inches Minimum And 0.262 Inches MaximumExpansion Device:Serrated Stem-type W
Shank Style:Self-plugging Mechanically Locked StemHead Major Diameter:0.238 Inches Minimum And 0.262 Inches MaximumExpansion Device:Serrated Stem-type W
Head Major Diameter: 0.238 Inches Minimum And 0.262 Inches Maximum Expansion Device: Serrated Stem-type W
Expansion Device: Serrated Stem-type W
Grin Length: 0.188 Inches Minimum And 0.250 Inches Maximum
0.100 menes minimum And 0.250 menes maximum
Special Features: Sleeve Color Orange No.32246,fed Std 595
Heat Treatment: H-38 Strain Hardened Locking Ring
Material: Aluminum Alloy 5056 Locking Ring
Material: Aluminum Alloy 5056 Sleeve
Material: Aluminum Alloy 7075 Stem
Material Document And Classification: Qq-a-430 Fed Spec Single Material Response Locking Ring
Material Document And Classification: Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification: Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment: Anodize Sleeve Or Chromate Sleeve
Surface Treatment: Anodize Stem Or Chromate Stem
Surface Treatment Document And Classification: Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification: Mil-a-8625 Mil Spec 1st Treatment Response Stem Or Mil-c-5541 Mil Spec 2nd Treatment Response Stem
Specification/standard Data: 80205-nas1398 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR2263-4-04 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.