

**Description**

diameter: 1/8", grip range: 0.188" - 0.250", wiredaw, universal head, 5056 aluminum sleeve, 7075 aluminum stem, CR2263 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR2263-4-4](#)

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | CR2263404           |
| Minimum Qty (MOQ):      | 100                 |
| NSN:                    | 5320-00-121-3045    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

## P/N CR2263-4-04 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.385 Inches Maximum   |
| <b>Head Style:</b>                                    | Universal  |
| <b>Head Height:</b>                                   | 0.054 Inches Minimum And 0.064 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.124 Inches Minimum And 0.128 Inches Maximum  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.238 Inches Minimum And 0.262 Inches Maximum  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Grip Length:</b>                                   | 0.188 Inches Minimum And 0.250 Inches Maximum  |
| <b>Special Features:</b>                              | Sleeve Color Orange No.32246,fed Std 595   |
| <b>Heat Treatment:</b>                                | H-38 Strain Hardened Locking Ring  |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Locking Ring   |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve   |
| <b>Material:</b>                                      | Aluminum Alloy 7075 Stem   |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Locking Ring  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Stem  |
| <b>Surface Treatment:</b>                             | Anodize Sleeve Or Chromate Sleeve  |
| <b>Surface Treatment:</b>                             | Anodize Stem Or Chromate Stem  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Stem Or Mil-c-5541 Mil Spec 2nd Treatment Response Stem     |
| <b>Specification/standard Data:</b>                   | 80205-nas1398 Professional/industrial Association Standard   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2263-4-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.