

Description

Fastener Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR2263-4-02](#)

| | |
|-------------------------|---------------------|
| SKU / Model: | CR226342 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-945-4746 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR2263-4-2 Specifications

| | |
|--|---|
| Fastener Length: | 0.260 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Nominal |
| Shank Diameter: | 0.125 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.250 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.063 Inches Minimum And 0.125 Inches Maximum |
| Heat Treatment: | H-38 Strain Hardened Locking Ring |
| Material: | Aluminum Alloy 5056 Locking Ring |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Aluminum Alloy 7075 Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Locking Ring |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Stem |
| Surface Treatment: | Anodize Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2263-4-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.