

Description

Fastener Length: 3/8", universal head, CR2263 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR2263-5-3](#)

SKU / Model:	CR2263503
Minimum Qty (MOQ):	100
NSN:	5320-00-993-7363
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N CR2263-5-03 Specifications

Fastener Length:	0.313 Inches Nominal
Head Style:	Universal
Head Height:	0.067 Inches Nominal
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.312 Inches Nominal
Expansion Device:	Knob Stem-type K
Grip Length:	0.187 Inches Maximum
Heat Treatment:	H-38 Strain Hardened Locking Ring
Material:	Aluminum Alloy 5056 Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Anodize Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2263-5-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.