

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR2263-6-4](#)

SKU / Model:

CR2263604

Minimum Qty (MOQ):

100

NSN:

5320-00-932-5717

ECCN:

EAR99

National Motor Freight:

061680, Elec Wiring Plugs Etc

NO IMAGE
AVAILABLE

P/N CR2263-6-04 Specifications

Fastener Length:	0.412 Inches Nominal
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.188 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Heat Treatment:	H-38 Strain Hardened Locking Ring
Material:	Aluminum Alloy 5056 Locking Ring
Material:	Aluminum Alloy 5056 Sleeve
Material:	Aluminum Alloy 7075 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2263-6-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.