

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	CR2539P42
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-113-1666
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CR2539P4-2 Specifications

<b>Fastener Length:</b>	0.255 Inches Minimum And 0.275 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.139 Inches Minimum And 0.143 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Shear Strength:</b>	750 Single Pounds Per Square Inch
<b>Material:</b>	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
<b>Material:</b>	Nickel Alloy 600 Stem
<b>Material:</b>	Nickel Alloy 400 Or Nickel Alloy R-405 Sleeve
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Sleeve
<b>Material Document And Classification:</b>	Qq-w-390 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment:</b>	Cadmium And Chromate Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Sleeve
<b>Specification/standard Data:</b>	80205-nas1738 Professional/industrial Association Standard

## How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2539P4-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.