



Military-Fasteners.com

P/N CR2539P4-6

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CR2539P46
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-093-8536
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR2539P4-6 Specifications

Fastener Length:	0.505 Inches Minimum And 0.525 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.139 Inches Minimum And 0.143 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.250 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Material:	Nickel Alloy Locking Ring
Material:	Nickel Alloy Stem
Material:	Nickel Alloy Body
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Body
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Material Document And Classification:	Qq-w-390 Fed Spec Single Material Response Stem
Surface Treatment:	Cadmium Body
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Fed Spec Single Treatment Response Body
Specification/standard Data:	80205-nas1738 Professional/industrial Association Standard

How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2539P4-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.