

Description

Fastener Length: 1/2", flush head, dry film,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2662-3-6](#)

SKU / Model:	CR2662306
Minimum Qty (MOQ):	100
NSN:	5320-01-345-3795
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N CR2662-3-06 Specifications

Fastener Length:	0.500 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.179 Inches Nominal
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ringiron Alloy 660 Sleeveiron Alloy 660 Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ringams 5732 Assn Std Single Material Response Sleeveams 5732 Assn Std Single Material Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2662-3-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.