

Description

Length: 0.542", dry film, flat head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2662-3-7](#)

SKU / Model:	CR2662307
Minimum Qty (MOQ):	100
NSN:	5320-01-476-3765
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N CR2662-3-07 Specifications

Fastener Length:	0.542 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.175 Inches Minimum And 0.183 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
End Item Identification:	F16aircombfit; F-16 Aircraft
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Dry Film Lube Per Mil-I-46010, Type I
Material:	Nickel Alloy Locking Ring
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams5731 Assn Std Single Material Response Stem
Material Document And Classification:	Ams5731 Assn Std Single Material Response Sleeve
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2662-3-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.