

**Description**

Length: 0.542", dry film, flat head

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR2662-3-7](#)

SKU / Model:	CR2662307
Minimum Qty (MOQ):	100
NSN:	5320-01-476-3765
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR2662-3-07 Specifications

<b>Fastener Length:</b>	0.542 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.175 Inches Minimum And 0.183 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>End Item Identification:</b>	F16aircombit; F-16 Aircraft
<b>Grip Length:</b>	0.376 Inches Minimum And 0.437 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Special Features:</b>	Dry Film Lube Per Mil-I-46010, Type I
<b>Material:</b>	Nickel Alloy Locking Ring
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Iron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Sleeve
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Locking Ring
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2662-3-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.