

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2662-5-03](#)

| | |
|-------------------------|--|
| SKU / Model: | CR266253 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-958-2897 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N CR2662-5-3 Specifications

| | |
|--|--|
| Fastener Length: | 0.303 Inches Minimum And 0.323 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.155 Inches Minimum And 0.159 Inches Maximum |
| Head Major Diameter: | 0.282 Inches Minimum And 0.290 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.126 Inches Minimum And 0.187 Inches Maximum |
| Shear Strength: | 1490 Single Pounds Per Square Inch |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Special Features: | Lock Ring Nickel-copper Alloy Qq-n-281 |
| Material: | Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Iron Alloy 660 Stem |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Sleeve |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Locking Ring |
| Specification/standard Data: | 80205-nas1399 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2662-5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.