

**Description**

Fastener Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR2662-5-04](#)

SKU / Model:	CR266254
Minimum Qty (MOQ):	100
NSN:	5320-00-054-8415
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR2662-5-4 Specifications

<b>Fastener Length:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.282 Inches Minimum And 0.290 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Shear Strength:</b>	1490 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Iron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams 5732 Assn Std Single Material Response Sleeve
<b>Material Document And Classification:</b>	Ams 5732 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Locking Ring
<b>Specification/standard Data:</b>	80205-nas1399 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2662-5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.