

Description

Fastener Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2662-5-06](#)

SKU / Model:	CR266256
Minimum Qty (MOQ):	100
NSN:	5320-00-783-4417
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR2662-5-6 Specifications

Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Special Features:	Lock Ring Nickel-copper Alloy Qq-n-281
Material:	Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ring

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2662-5-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.