

Description

Fastener Length: 3/8", CR2662 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR2662-6-04](#)

| | |
|-------------------------|---|
| SKU / Model: | CR266264 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-995-1177 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N CR2662-6-4 Specifications

| | |
|--|--|
| Fastener Length: | 0.375 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.188 Inches Nominal |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.353 Inches Nominal |
| Expansion Device: | Knob Stem-type K |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Iron Alloy 660 Stem |
| Material: | Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring |
| Material Document And Classification: | Aams 5732 Assn Std All Material Responses Sleeve |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Locking Ring |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2662-6-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.