

Description

Fastener Length: 1/4", CR2663 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR2663-3-1](#)

| | |
|-------------------------|---|
| SKU / Model: | CR2663301 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-117-7790 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N CR2663-3-01 Specifications

| | |
|--|--|
| Fastener Length: | 0.232 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Shank Diameter: | 0.093 Inches Minimum And 0.097 Inches Maximum |
| Head Major Diameter: | 0.178 Inches Minimum And 0.196 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| Grip Length: | 0.025 Inches Minimum And 0.062 Inches Maximum |
| Material: | Nickel Alloy X-750 Locking Ring Or Nickel Alloy R-405 Locking Ring |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Iron Alloy 660 Stem |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Sleeve |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Locking Ring |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2663-3-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.