



★ FASTENERS

Military-Fasteners.com

P/N CR2663-3-04

Description

CR2663 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2663-3-4](#)

SKU / Model:

CR2663304

Minimum Qty (MOQ):

100

NSN:

5320-01-488-3868

Schedule B:

7318.23.0000

ECCN:

EAR99



* See page 2 for technical characteristics

P/N CR2663-3-04 Specifications

| | |
|---|---|
| Fastener Length: | 0.354 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Shank Diameter: | 0.093 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.178 Inches Minimum And 0.196 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| End Item Identification: | F-22 Raptor |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Iron Alloy 660 Stem |
| Material: | Nickel Alloy 400 Locking Ring |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Sleeve |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Locking Ring |
| Surface Treatment: | Passivate Sleeve |
| Surface Treatment: | Passivate Stem |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2663-3-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.