

Description

Fastener Length: 1/4", CR2663 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR2663-3-02](#)

SKU / Model:	CR266332
Minimum Qty (MOQ):	100
NSN:	5320-01-132-4439
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR2663-3-2 Specifications

Fastener Length:	0.295 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ring

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2663-3-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.