

Description

wiredaw, universal head, a-286 corrosion resistant sleeve and stem, monel lock ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR2663-4-2](#)

SKU / Model:	CR2663402
Minimum Qty (MOQ):	100
NSN:	5320-00-880-3334
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR2663-4-02 Specifications

Fastener Length:	0.260 Inches Nominal
Head Style:	Oval Washer
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.125 Inches Nominal
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Plain Stem-type T
Lubrication:	Dry Film
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Material:	Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Locking Ring

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2663-4-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.