

**Description**

Fastener Length: 3/8", CR2663 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[NAS1398C4-4](#) [CR2663-4-4](#)

SKU / Model:	CR2663404
Minimum Qty (MOQ):	100
NSN:	5320-00-027-3754
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CR2663-4-04 Specifications

<b>Fastener Length:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.125 Inches Nominal
<b>Heat Treatment:</b>	As Fabricated Overall
<b>Material:</b>	Steel Body
<b>Material:</b>	Steel Stem
<b>Material Document And Classification:</b>	Ams 5736 Assn Std 2nd Material Response Stem
<b>Material Document And Classification:</b>	Ams 5735 Assn Std 1st Material Response Body
<b>Surface Treatment:</b>	Any Acceptable Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2663-4-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.