

Description

Fastener Length: 3/8", CR2663 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[NAS1398C4-4](#) [CR2663-4-04](#)

SKU / Model:	CR266344
Minimum Qty (MOQ):	100
NSN:	5320-00-027-3754
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N CR2663-4-4 Specifications

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.125 Inches Nominal
Heat Treatment:	As Fabricated Overall
Material:	Steel Body
Material:	Steel Stem
Material Document And Classification:	Ams 5736 Assn Std 2nd Material Response Stem
Material Document And Classification:	Ams 5735 Assn Std 1st Material Response Body
Surface Treatment:	Any Acceptable Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2663-4-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.