

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR2663-5-2](#)

| | |
|-------------------------|---|
| SKU / Model: | CR2663502 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-835-6332 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR2663-5-02 Specifications

| | |
|--|--|
| Fastener Length: | 0.263 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.063 Inches Minimum And 0.125 Inches Maximum |
| Material: | Nickel Alloy R-405 Locking Ring Or Nickel Alloy 400 Locking Ring |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Iron Alloy 660 Stem |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Sleeve |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281 Fed Spec All Material Responses Locking Ring |
| Surface Treatment: | Passivate Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2663-5-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.