

Description

Fastener Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CR266385
Minimum Qty (MOQ):	100
NSN:	5320-00-021-4108
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR2663-8-5 Specifications

Fastener Length:	0.510 Inches Maximum
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.253 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Stem
Specification/standard Data:	80205-nas1398 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR2663-8-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.