

P/N CR3212-4-02

Description

Diameter: 1/8", grip range: 0.063" - 0.125", flush head, aluminum sleeve, steel stem, CherryMax, CR3212402, Use G27 installation tool

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CR3212-4-2

SKU / Model:	CR3212402
Minimum Qty (MOQ):	100
NSN:	5320-01-085-3321
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N CR3212-4-02 Specifications

0.189 Inches Minimum And 0.209 Inches Maximum
Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
0.125 Inches Minimum And 0.129 Inches Maximum
Self-plugging Mechanically Locked Stem
0.229 Inches Maximum
Serrated Stem-type W
0.051 Inches Minimum And 0.125 Inches Maximum
99.0 Degrees Minimum And 101.0 Degrees Maximum
Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Aluminum Alloy 5056 Sleeve
Steel Comp 8740 Stem
Ams 6322 Assn Std Single Material Response Stem
Qq-a-430 Fed Spec Single Material Response Sleeve
Chromate Sleeve
Cadmium Stem And Chromate Stem
Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3212-4-02 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.