

P/N CR3212-4-07

Military-Fasteners.com

### Description

diameter: 1/8", grip range: 0.376" - 0.437", flush head, aluminum sleeve, steel stem

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

CR	321	12-4	-7

SKU / Model:	CR3212407
Minimum Qty (MOQ):	100
NSN:	5320-01-126-2660
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



# P/N CR3212-4-07 Specifications

Fastener Length:	0.527 Inches Minimum And 0.547 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.125 Inches Minimum And 0.129 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Helicopter Observation (ahip), Oh-58d; Aircraft, B-2 Bomber (atb); Aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130; Aircraft, Phantom F-4; Aircraft, Airlifter C-17a; Support Equipment, B-1 Aircraft; Aircraft Mh-47e; Support Equipment (se), B-2 Bomber; F/a-18e/f Hornet Aircraft; Missle, Vehicle Mounter Stinger (avenger)
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Stem

# How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/CR3212-4-07</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.