

P/N CR3212-6-02

Military-Fasteners.com

Description

diameter: 3/16", grip range: 0.063" - 0.125", flush head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS9302B6-02 CR3212-6-2

SKU / Model:	CR3212602
Minimum Qty (MOQ):	100
NSN:	5320-01-163-0179
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N CR3212-6-02 Specifications

Head Style:Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)Shank Diameter:0.110 Inches NominalShank Style:Self-plugging Mechanically Locked StemHead Major Diameter:0.349 Inches Minimum And 0.357 Inches MaximumExpansion Device:Serrated Stem-type WGrip Length:0.080 Inches Minimum And 0.125 Inches MaximumMinimum Tensile Strength:635 Pounds Per Square InchCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSpecial Features:Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.Material:Iron Alloy 506 SleeveMaterial:Toon Alloy 560 Locking RingMaterial Document And Classification:Ams6322 Assn Std Single Material Response StemMaterial Document And Classification:Ams5731 Assn Std Single Material Response Locking RingMaterial Document And Classification:Ams6322 Assn Std Single Material Response Steme		
Shank Diameter:0.110 Inches NominalShank Style:Self-plugging Mechanically Locked StemHead Major Diameter:0.349 Inches Minimu And 0.357 Inches MaximumExpansion Device:Serrated Stem-type WGrip Length:0.080 Inches Minimu And 0.125 Inches MaximumMinimum Tensile Strength:635 Pounds Per Square InchCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSpecial Features:Winidicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal). Rivets With No Letter CodeMaterial:Aluminum Alloy 5056 SleeveMaterial:Iron Alloy 660 Locking RingMaterial Document And Classification:Ams5731 Assn Std Single Material Response Locking RingMaterial Document And Classification:Ams5731 Assn Std Single Material Response Locking RingMaterial Document And Classification:Conc.430 Eed Sper Single Material Response Sleeve	Fastener Length:	0.193 Inches Nominal
Shank Style:Self-plugging Mechanically Locked StemHead Major Diameter:0.349 Inches Minimum And 0.357 Inches MaximumExpansion Device:Serrated Stem-type WGrip Length:0.080 Inches Minimum And 0.125 Inches MaximumMinimum Tensile Strength:635 Pounds Per Square InchCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSpecial Features:(indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.Material:Aluminum Alloy 5056 SleeveMaterial:Stel Comp 8740 StemMaterial Document And Classification:Stel Comp 8740 StemMaterial Document And Classification:Ams5731 Assn Std Single Material Response Locking RingMaterial Document And Classification:Ams6322 Assn Std Single Material Response Sleave	Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Head Major Diameter:0.349 Inches Minimum And 0.357 Inches MaximumExpansion Device:Serrated Stem-type WGrip Length:0.080 Inches Minimum And 0.125 Inches MaximumMinimum Tensile Strength:635 Pounds Per Square InchCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSpecial Features:Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter CodeSpecial Features:Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter CodeMaterial:Aluminum Alloy 5056 SleeveMaterial:Iron Alloy 660 Locking RingMaterial Document And Classification:Ams6322 Assn Std Single Material Response StemMaterial Document And Classification:Ams5731 Assn Std Single Material Response Locking RingMaterial Document And Classification:Ona-430 End Spar Single Material Response Steme	Shank Diameter:	0.110 Inches Nominal
Expansion Device:Serrated Stem-type WGrip Length:0.080 Inches Minimum And 0.125 Inches MaximumMinimum Tensile Strength:635 Pounds Per Square InchCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSpecial Features:Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter CodeSpecial Features:Nininum Alloy 5056 SleeveMaterial:Aluminum Alloy 5056 SleeveMaterial:Iron Alloy 660 Locking RingMaterial:Steel Comp 8740 StemMaterial Document And Classification:Ams5731 Assn Std Single Material Response Locking RingMaterial Document And Classification:Ona-430 East Sper Single Material Response Sleave	Shank Style:	Self-plugging Mechanically Locked Stem
Grip Length:0.080 Inches Minimu And 0.125 Inches MaximumMinimum Tensile Strength:635 Pounds Per Square InchCountersink Angle:99.0 Degrees Minimu And 101.0 Degrees MaximumSpecial Features:Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter CodeSpecial Features:Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter CodeMaterial:Aluminum Alloy 5056 SleeveMaterial:Iron Alloy 660 Locking RingMaterial Document And Classification:Ams6322 Assn Std Single Material Response StemMaterial Document And Classification:Ams5731 Assn Std Single Material Response Sleave	Head Major Diameter:	0.349 Inches Minimum And 0.357 Inches Maximum
Ninimum Tensile Strength:635 Pounds Per Square InchCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSpecial Features:Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.Material:Aluminum Alloy 5056 SleeveMaterial:Iron Alloy 660 Locking RingMaterial Document And Classification:Ams6322 Assn Std Single Material Response StemMaterial Document And Classification:Ams5731 Assn Std Single Material Response Sleeve	Expansion Device:	Serrated Stem-type W
Countersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSpecial Features:Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.Material:Aluminum Alloy 5056 SleeveMaterial:Iron Alloy 660 Locking RingMaterial Document And Classification:Ams6322 Assn Std Single Material Response StemMaterial Document And Classification:Ams5731 Assn Std Single Material Response Locking Ring	Grip Length:	0.080 Inches Minimum And 0.125 Inches Maximum
Special Features:Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.Material:Aluminum Alloy 5056 SleeveMaterial:Iron Alloy 660 Locking RingMaterial Document And Classification:Steel Comp 8740 StemMaterial Document And Classification:Ams5731 Assn Std Single Material Response Locking RingMaterial Document And Classification:Ams5731 Assn Std Single Material Response Sleeve	Minimum Tensile Strength:	635 Pounds Per Square Inch
Special Features:(indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.Material:Aluminum Alloy 5056 SleeveMaterial:Iron Alloy 660 Locking RingMaterial Document And Classification:Steel Comp 8740 StemMaterial Document And Classification:Ams5731 Assn Std Single Material Response Locking RingMaterial Document And Classification:Occa-430 Eed Spec Single Material Response Sleeve	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material: Iron Alloy 660 Locking Ring Material: Steel Comp 8740 Stem Material Document And Classification: Ams6322 Assn Std Single Material Response Stem Material Document And Classification: Ams5731 Assn Std Single Material Response Locking Ring Material Document And Classification: Og.az.430 Eed Spec Single Material Response Sleeve	Special Features:	(indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For
Material: Steel Comp 8740 Stem Material Document And Classification: Ams6322 Assn Std Single Material Response Stem Material Document And Classification: Ams5731 Assn Std Single Material Response Locking Ring Material Document And Classification: On-a-430 Eed Spec Single Material Response Sleeve	Material:	Aluminum Alloy 5056 Sleeve
Material Document And Classification: Ams6322 Assn Std Single Material Response Stem Material Document And Classification: Ams5731 Assn Std Single Material Response Locking Ring Material Document And Classification: Og.az.430 Eed Spec Single Material Response Sleeve	Material:	Iron Alloy 660 Locking Ring
Classification: Ams6322 Assn Std Single Material Response Stem Material Document And Ams5731 Assn Std Single Material Response Locking Ring Material Document And Og.a.430 Eed Spec Single Material Response Sleeve	Material:	Steel Comp 8740 Stem
Classification: Ams5731 Assn Std Single Material Response Locking Ring Material Document And Og.a.430 Fed Spec Single Material Response Sleeve	Material Document And Classification:	Ams6322 Assn Std Single Material Response Stem
Ogra-130 Fed Sner Single Material Response Sleeve	Material Document And Classification:	Ams5731 Assn Std Single Material Response Locking Ring
Classification:	Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment: Chromate Sleeve	Surface Treatment:	Chromate Sleeve
Surface Treatment: Cadmium Stem	Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Da-n-416 Fed Spec Single Treatment Response Stem	Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/CR3212-6-02</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.