

Description

diameter: 3/16", grip range: 0.251" - 0.312", flush head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3212-6-5](#)

SKU / Model:

CR3212605

Minimum Qty (MOQ):

100

NSN:

5320-01-606-0089

ECCN:

EAR99



P/N CR3212-6-05 Specifications

Head Style:	Cooper's (included Angle - 135 Deg And Over)
Head Height:	0.053 Inches Nominal
Hole Diameter:	0.160 Inches Minimum And 0.164 Inches Maximum
Shank Diameter:	0.156 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.267 Inches Nominal
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Rivet
Material:	Steel Corrosion Resisting Body
Supplementary Features:	Stainless Steel, 100 Deg Csk Head Ms20426

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3212-6-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.