

Description

diameter: 3/16", grip range: 0.251" - 0.312", flush head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3212-6-5](#)

SKU / Model:

CR3212605

Minimum Qty (MOQ):

100

NSN:

5320-01-606-0089

ECCN:

EAR99



P/N CR3212-6-05 Specifications

| | |
|--|--|
| Head Style: | Cooper's (included Angle - 135 Deg And Over) |
| Head Height: | 0.053 Inches Nominal |
| Hole Diameter: | 0.160 Inches Minimum And 0.164 Inches Maximum |
| Shank Diameter: | 0.156 Inches Minimum And 0.159 Inches Maximum |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.267 Inches Nominal |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Part Name Assigned By Controlling Agency: | Rivet |
| Material: | Steel Corrosion Resisting Body |
| Supplementary Features: | Stainless Steel, 100 Deg Csk Head Ms20426 |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3212-6-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.