

P/N CR3212-6-05

Description

diameter: 3/16", grip range: 0.251" - 0.312", flush head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CR3212-6-5

SKU / Model: CR3212605

Minimum Qty (MOQ):

NSN: 5320-01-606-0089

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N CR3212-6-05 Specifications

Head Style:	Cooper's (included Angle - 135 Deg And Over)
Head Height:	0.053 Inches Nominal
Hole Diameter:	0.160 Inches Minimum And 0.164 Inches Maximum
Shank Diameter:	0.156 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.267 Inches Nominal
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Rivet
Material:	Steel Corrosion Resisting Body
Supplementary Features:	Stainless Steel, 100 Deg Csk Head Ms20426

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3212-6-05 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3212-6-05 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3212-6-05 and selecting the quantity you want then click "add to cart".