

**Description**

diameter: 3/16", grip range: 0.376" - 0.437", flush head, 5056 aluminum sleeve, steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CR3212-6-7](#)

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | CR3212607           |
| Minimum Qty (MOQ):      | 100                 |
| NSN:                    | 5320-01-086-1147    |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

## P/N CR3212-6-07 Specifications

|   |   |
|---|---|
| <b>Fastener Length:</b>                               | 0.565 Inches Minimum And 0.585 Inches Maximum   |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)  |
| <b>Shank Diameter:</b>                                | 0.188 Inches Minimum And 0.192 Inches Maximum   |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem  |
| <b>Head Major Diameter:</b>                           | 0.357 Inches Maximum  |
| <b>Expansion Device:</b>                              | Serrated Stem-type W  |
| <b>Grip Length:</b>                                   | 0.376 Inches Minimum And 0.437 Inches Maximum   |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum  |
| <b>Special Features:</b>                              | Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply. |
| <b>Material:</b>                                      | Aluminum Alloy 5056 Sleeve  |
| <b>Material:</b>                                      | Steel Comp 8740 Stem  |
| <b>Material Document And Classification:</b>          | Ams 6322 Assn Std Single Material Response Stem   |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec Single Material Response Sleeve   |
| <b>Surface Treatment:</b>                             | Chromate Sleeve   |
| <b>Surface Treatment:</b>                             | Cadmium Stem And Chromate Stem  |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-5541 Mil Spec Single Treatment Response Sleeve  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Stem   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3212-6-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.