

P/N CR3212-6-09

Description

diameter: 3/16", grip range: 0.501" - 0.562", flush head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CR3212-6-9

SKU / Model: CR3212609

Minimum Qty (MOQ): 100

NSN: 5320-01-086-1145

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N CR3212-6-09 Specifications

Fastener Length:	0.690 Inches Minimum And 0.710 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.188 Inches Minimum And 0.192 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.357 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Wsd: Aircraft, Stratolifter C-135; Aircraft, Hornet F/a-18; Aircraft, Hercules C-130; Aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130; Aircraft, Thunderbolt Ii, A-10; Cryogenic Systems; Helicopter Observation (ahip), Oh-58d; Aircraft, Phantom F-4; Aircraft, F-16; Low Altitude Navigation And Targetinginfra Red System (lantim)
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Criticality Code Justification:	Feat
Special Features:	Weapon System Essential
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Stem

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3212-6-09 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3212-6-09 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3212-6-09 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3212-6-09 and selecting the quantity you want then