

Description

flush flat head, aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3212-8-8](#)

SKU / Model:	CR3212808
Minimum Qty (MOQ):	100
NSN:	5320-01-339-4084
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR3212-8-08 Specifications

Fastener Length:	0.607 Inches Minimum And 0.637 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.252 Inches Minimum And 0.258 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.472 Inches Minimum And 0.480 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve Steel Comp 8740 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeveams 6322 Assn Std Single Material Response Stem
Surface Treatment:	Chromate Sleeve cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve qq-p-416, ty 2, cl 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3212-8-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.