

**Description**

flush flat head, aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3212-8-8](#)

SKU / Model:	CR3212808
Minimum Qty (MOQ):	100
NSN:	5320-01-339-4084
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CR3212-8-08 Specifications

<b>Fastener Length:</b>	0.607 Inches Minimum And 0.637 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.252 Inches Minimum And 0.258 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.472 Inches Minimum And 0.480 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.438 Inches Minimum And 0.500 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 5056 Sleeve Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeveams 6322 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Chromate Sleeve cadmium Stem And Chromate Stem
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Sleeve qq-p-416, ty 2, cl 2 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3212-8-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.