

Description

diameter: 1/8", grip range: 0.126" - 0.187", universal head, nominal diameter, head markings and lock collar are visible after the installation, the gold color driving anvil identifies the nominal diameter rivet type, aluminum sleeve per QQ-A-430, steel stem per AMS6322, A-286 cres per AMS5731 and AMS5737 lock collar, Use G27 installation tool, CherryMax, CR3213402, CR3213 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3213-4-3](#)

SKU / Model:	CR3213403
Minimum Qty (MOQ):	100
NSN:	5320-01-138-4239
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N CR3213-4-03 Specifications

Fastener Length:	0.277 Inches Minimum And 0.297 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.125 Inches Minimum And 0.129 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Special Features:	"ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3213-4-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.