

Description

diameter: 1/8", grip range: 0.313" - 0.375", universal head, aluminum sleeve, steel stem, CR3213 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3213-4-6](#)

| | |
|-------------------------|---------------------|
| SKU / Model: | CR3213406 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-086-3597 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N CR3213-4-06 Specifications

| | |
|---|---|
| Fastener Length: | 0.439 Inches Minimum And 0.459 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.125 Inches Minimum And 0.129 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| End Item Identification: | Aircraft, Phantom F-4; Low Altitude Navigation & Targeting Infrared System (lantrin); Aircraft, Hercules C-130; Milstar System; F414 Engine (f/a-18 F& G Aircraft); Aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130; Helicopter, Mh-53e; Helicopter, Advance Attack, Ah-1w; Aircraft, Stratolifter C-135; Aircraft, Stratofortress B-52 |
| Grip Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Special Features: | Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply. |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Comp 8740 Stem |
| Material Document And Classification: | Ams 6322 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Surface Treatment: | Chromate Sleeve |
| Surface Treatment: | Cadmium Stem And Chromate Stem |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec Single Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3213-4-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.