

Description

diameter: 1/8", grip range: 0.501" - 0.562", universal head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3213-4-9](#)

SKU / Model:	CR3213409
Minimum Qty (MOQ):	100
NSN:	5320-01-263-4360
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N CR3213-4-09 Specifications

Fastener Length:	0.632 Inches Minimum And 0.662 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.125 Inches Minimum And 0.129 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Low Altitude Navigation & Targeting Infrared System(lantirn);helicopter,lamps Mark Iii, Sh-60b;aircraft, Hercules C-130;milstar System
Grip Length:	0.501 Nominal Mils And 0.562 Nominal Centimeters
Special Features:	"ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3213-4-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.