

P/N CR3213-5-03

Description

diameter: 5/32", grip range: 0.126" - 0.187", universal head, aluminum sleeve, steel stem, use G27 installation tool, CR3213503, CR3213 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CR3213-5-3

SKU / Model:	CR3213503
Minimum Qty (MOQ):	100
NSN:	5320-01-133-5889
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets









P/N CR3213-5-03 Specifications

Fastener Length:	0.283 Inches Minimum And 0.303 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.156 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Special Features:	Ns Letters After The Material Code B Indicate No Preference To Lock Type; May Be Visible Or Internal; Rivets With No Letter Code; Indicating Visible Lock Type; And Rivets With The Letter H After The Material Code; Indicating Internal Lock Type; Are Both Acceptable For This Item Of Supply
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3213-5-03 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.