

# P/N CR3213-6-04

## **Description**

diameter: 3/16", grip range: 0.188" - 0.25", universal head, aluminum sleeve, steel stem, CR3213 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

## **Additional Information**

#### **Alternate Part Numbers**

### CR3213-6-4

SKU / Model: CR3213604

Minimum Qty (MOQ): 100

NSN: 5320-01-136-1782

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 013630, Alum Rivets









# P/N CR3213-6-04 Specifications

0.377 Inches Minimum And 0.397 Inches Maximum
Universal
0.080 Inches Minimum And 0.090 Inches Maximum
0.188 Inches Minimum And 0.192 Inches Maximum
Self-plugging Mechanically Locked Stem
0.365 Inches Minimum And 0.385 Inches Maximum
Serrated Stem-type W
0.188 Inches Minimum And 0.250 Inches Maximum
Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Aluminum Alloy 5056 Sleeve
Steel Comp 8740 Stem
Ams 6322 Assn Std Single Material Response Stem
Qq-a-430 Fed Spec Single Material Response Sleeve
Chromate Sleeve
Cadmium Stem And Chromate Stem
Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Stem

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/CR3213-6-04">https://military-fasteners.com/rivets/blind+rivets/CR3213-6-04</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.