

P/N CR3213-6-06

Description

diameter: 3/16", grip range: 0.313" - 0.375", universal head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CR3213-6-6

SKU / Model: CR3213606

Minimum Qty (MOQ): 100

NSN: 5320-01-084-9234

ECCN: EAR99

National Motor Freight: 013630, Alum Rivets









^{*} See page 2 for technical characteristics

P/N CR3213-6-06 Specifications

Fastener Length:	0.502 Inches Minimum And 0.522 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.192 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Aircraft, Stratolifter C-135;aircraft, Hercules C-130;aircraft, Hercules C-130;forrestal Class Cv;radio Terminal, Digital Troposcatter (an/trc-170);aircraft, Ac-130h, Mc-130h, Ec-130e, Hc-130;cryogenic Systems;wasp Class Lhd;aircraft,b-2 Bomber (atb)
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Special Features:	Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Stem

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3213-6-06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3213-6-06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3213-6-06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CR3213-6-06 and selecting the quantity you want then