

P/N CR3213-6-08

Description

diameter: 3/16", grip range: 0.438" - 0.500", universal head, 5056 aluminum sleeve, steel stem, CR3213 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CR3213-6-8

SKU / Model:	CR3213608
Minimum Qty (MOQ):	100
NSN:	5320-01-086-1144
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

^{*} See page 2 for technical characteristics

P/N CR3213-6-08 Specifications

0.627 Inches Minimum And 0.647 Inches Maximum
Universal
0.080 Inches Minimum And 0.090 Inches Maximum
0.188 Inches Minimum And 0.192 Inches Maximum
Self-plugging Mechanically Locked Stem
0.365 Inches Minimum And 0.385 Inches Maximum
Serrated Stem-type W
0.438 Inches Minimum And 0.500 Inches Maximum
Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Aluminum Alloy 5056 Sleeve
Steel Comp 8740 Stem
Ams 6322 Assn Std Single Material Response Stem
Qq-a-430 Fed Spec Single Material Response Sleeve
Chromate Sleeve
Cadmium Stem And Chromate Stem
Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Stem

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3213-6-08 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.