

Description

diameter: 3/16", grip range: 0.501" - 0.562", universal head, aluminum sleeve, steel stem, CR3213 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[CR3213-6-9](#)

SKU / Model:	CR3213609
Minimum Qty (MOQ):	100
NSN:	5320-01-225-7791
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR3213-6-09 Specifications

Fastener Length:	0.670 Inches Minimum And 0.730 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.192 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Expansion Device:	Break Head
End Item Identification:	Uw/s: Aircraft, B-2 Bomber (atb); Missile, Vehicle Mounted Stinger (avenger); Sentinel Radar System; Aircraft, Hx Unique; Thermal Imagery - Mctns; Low Altitude Navigation & Targeting Infrared System (Iantirn); Aircraft, Galaxy C-5
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Special Features:	Ns" Letters After The Material Code "b" Indicate No Preference To Lock Type (may Be Visible Or Internal). Rivets With No Letter Code (indicating Visible Lock Type) And Rivets With The Letter "h" After The Material Code (indicating Internal Lock Type) Are Both Acceptable For This Item Of Supply.
Material:	Aluminum Alloy 5056 Sleeve
Material:	Iron Alloy 660 Collar
Specification/standard Data:	81349--7885/2-6-9 Government Specification

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3213-6-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.