

**Description**

diameter: 1/4", grip range: 0.126" - 0.187", universal head, aluminum sleeve, steel stem

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[CR3213-8-3](#)

SKU / Model:	CR3213803
Minimum Qty (MOQ):	100
NSN:	5320-01-338-4194
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CR3213-8-03 Specifications

<b>Fastener Length:</b>	1.737 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.107 Inches Minimum And 0.117 Inches Maximum
<b>Shank Diameter:</b>	0.252 Inches Minimum And 0.256 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Minimum Tensile Strength:</b>	1125000 Pounds Per Square Inch
<b>Shear Strength:</b>	2615 Single Pounds Per Square Inch
<b>Material:</b>	Iron Alloy 660 Collaraluminum Alloy 5056 Sleevesteel Comp 8740 Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Collarqq-a-430 Fed Spec Single Material Response Sleeveams 6322 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Chromate Sleevecadmium Stem And Chromate Stem
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Sleeveqq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3213-8-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.