

Description

diameter: 1/4", grip range: 0.126" - 0.187", universal head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CR3213-8-3](#)

SKU / Model:	CR3213803
Minimum Qty (MOQ):	100
NSN:	5320-01-338-4194
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CR3213-8-03 Specifications

Fastener Length:	1.737 Inches Nominal
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.252 Inches Minimum And 0.256 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.490 Inches Minimum And 0.510 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Minimum Tensile Strength:	1125000 Pounds Per Square Inch
Shear Strength:	2615 Single Pounds Per Square Inch
Material:	Iron Alloy 660 Collaraluminum Alloy 5056 Sleevesteel Comp 8740 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Collarqq-a-430 Fed Spec Single Material Response Sleeveams 6322 Assn Std Single Material Response Stem
Surface Treatment:	Chromate Sleeveadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeveqq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3213-8-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.