

**Description**

CR3213-8-07 Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3213-8-7](#)

SKU / Model:	CR3213807
Minimum Qty (MOQ):	100
NSN:	5320-01-275-1097
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CR3213-8-07 Specifications

<b>Fastener Length:</b>	1.977 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.107 Inches Minimum And 0.117 Inches Maximum
<b>Shank Diameter:</b>	0.252 Inches Minimum And 0.256 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.4375 Inches Maximum
<b>Minimum Tensile Strength:</b>	1125000 Pounds Per Square Inch
<b>Shear Strength:</b>	2615 Single Pounds Per Square Inch
<b>Material:</b>	Aluminum Alloy 5052 Sleeve
<b>Material:</b>	Iron Alloy 660 Collar
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Ams 6322 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Collar
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Surface Treatment:</b>	Chromate Sleeve
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3213-8-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.