

Description

CR3213-8-07 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR3213-8-7](#)

SKU / Model:	CR3213807
Minimum Qty (MOQ):	100
NSN:	5320-01-275-1097
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CR3213-8-07 Specifications

Fastener Length:	1.977 Inches Nominal
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.252 Inches Minimum And 0.256 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.490 Inches Minimum And 0.510 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.4375 Inches Maximum
Minimum Tensile Strength:	1125000 Pounds Per Square Inch
Shear Strength:	2615 Single Pounds Per Square Inch
Material:	Aluminum Alloy 5052 Sleeve
Material:	Iron Alloy 660 Collar
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Collar
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3213-8-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.