

Description

diameter: 1/4", grip range: 0.438" - 0.500", universal head, aluminum sleeve, steel stem

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

CR3213-8-8

SKU / Model:	CR3213808
Minimum Qty (MOQ):	100
NSN:	5320-01-393-0842
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N CR3213-8-08 Specifications

Identification Code Color:	Natural
Fastener Length:	0.690 Inches Maximum
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.253 Inches Maximum
Head Major Diameter:	0.490 Inches Minimum And 0.510 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	W/s:aircraft, Thunderbolt li, A-10
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Iron Alloy 660 Locking Ring
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Locking Ring
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment:	Passivate Locking Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Qq-p-416, Type li, Class 2. Fed Spec Single Treatment Response Stem
Specification/standard Data:	53551-af3213 Manufacturers Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CR3213-8-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.