

P/N CR3214-4-02

Description

diameter: 1/8", grip range: 0.063" - 0.125", nas1097 style, flush head, aluminum sleeve, steel stem, CherryMax, CR3214 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CR3214-4-2

SKU / Model:	CR3214402
Minimum Qty (MOQ):	100
NSN:	5320-01-258-6058
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



^{*} See page 2 for technical characteristics

P/N CR3214-4-02 Specifications

Factor on Louisth.	1 220 In ale as Nameinal
Fastener Length:	1.320 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Head Major Diameter:	0.188 Inches Minimum And 0.196 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	W/s: Aircraft, F-111; Aircraft, Intruder A-6e; Ah-64-d Longbow; Helicopter, Apache Ah-64; Aircraft, Thunderbolt Ii, A-10; Helicopter, Utility/search And Recovery Un-1n
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CR3214-4-02 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.